

INDI PLUS

L80 B10 >54 000h | SDCM 3 | LLMF 85% | CRI 80-90+

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	COLOUR TEMPERATURE	ORDER REFERENCE
INDI PLUS 50	48W	5210 Lm	109 lm/W	1117 x 1117 x 57 x 75 mm	3000K	INDP50
INDI PLUS 50	48W	5320 Lm	111 lm/W	1117 x 1117 x 57 x 75 mm	4000K	INDP50

*Values are given for HEX diffuser, CRI 80 and may vary for other options

MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey

DIFFUSER - OPQ-Opal/Polycarbonate, HEX-Micro-prismatic/PMMA




INSTALLATION

Suspended

FIXINGS

	INFO	CODE
End Cap	Single/Metal*	INDI-ENDCAP
	Single/PC	INDI-ENDCAP-S
Joints	Inline	INDI-JOINT-I
	Corner 90°*	INDI-JOINT-C
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical*	ZLISS-SUSP

*Any RAL colour option available. Order example: **INDI-ENDCAP-GR**



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Micro-prismatic	HEX
Opal	OPQ
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
EMERGENCY MODULE	
3 hr	EM
CRI	
≥ 90	C90

Order code example: **INDP50-4K-ST-HEX-GR**