



## COFFEX

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
COFFEX 15	17W	1620 Lm	95 lm/W	595 x 134 x 87 mm	COFF15
COFFEX 30	31W	3190 Lm	102 lm/W	595 x 134 x 87 mm	COFF30
COFFEX 35	31W	3600 Lm	116 lm/W	1195 x 134 x 87 mm	COFF35
COFFEX 65	60W	6600 Lm	110 lm/W	1195 x 134 x 87 mm	COFF65

\*Values are given for colour temperature of 4000K / OPQ diffuser, and may variate for other options

### MATERIALS

CASING - powder painted steel sheet; standard colour - white

DIFFUSER - PC

### INSTALLATION

Into modular ceilings 600x600 with a visible supporting structure

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### DIFFUSER

Opal OPQ

Parabolic Louvers PAR

#### CASING COLOUR

White WH


Grey GR

Black BL

Custom RAL

#### EMERGENCY MODULE

3 hr EM



Order code example: **COFF30-4K-DL-QPQ-WH-EM**