




## LITHIUM LITE



L80 B10 > 72 000h | SDCM 3 | LLMF 86% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE		ORDER REFERENCE
LITHIUM LITE 10	10W	1120 Lm	112 lm/W	Ø 195 x 102 mm	180 mm	LILI10
LITHIUM LITE 15	15W	1530 Lm	102 lm/W	Ø 195 x 102 mm		LILI15
LITHIUM LITE 20	19W	2000 Lm	105 lm/W	Ø 235 x 111 mm	220 mm	LILI20
LITHIUM LITE 30	28W	2710 Lm	97 lm/W	Ø 235 x 111 mm		LILI30

\*Values are given for 4000K colour temperature and may vary for other options

### MATERIALS

CASING - aluminium

DIFFUSER - PMMA

REFLECTOR - mat aluminium with a purity of 99,85%

### INSTALLATION

Recessed into the modular ceiling

Recessed into plaster-cardboard



### ORDER CODE

#### COLOUR TEMPERATURE

3000K      3K

4000K      4K

#### DRIVER TYPE

Standard      ST

Dimming - DALI      DL

#### EMERGENCY MODULE

3 hr      EM

Order code example: **LILI20-4K-DL**