



## VELLA LED

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT	EFFICACY	TYPE OF LENS	PROTECTION LEVEL	PRODUCT SIZE	ORDER CODE FOR WHITE	ORDER CODE FOR BLACK
VELLA LED SO 150 M/ NM 3H AT IP44	6W	190 Lm	32 lm/W	SO	IP44	269 x 144 x 42 mm	93506	93628
VELLA LED SO 150 M/ NM 3H AT IP65	5W	190 Lm	38 lm/W	SO	IP65	269 x 144 x 42 mm	93508	93622
VELLA LED SO 250 M/ NM 3H AT IP44	8W	331 Lm	41 lm/W	SO	IP44	269 x 144 x 42 mm	93518	93592
VELLA LED SO 250 M/ NM 3H AT IP65	7W	331 Lm	47 lm/W	SO	IP65	269 x 144 x 42 mm	93520	93615
VELLA LED SO 350 M/ NM 3H AT IP65	8W	368 Lm	46 lm/W	SO	IP65	269 x 144 x 42 mm	93525	93607
VELLA LED SO 350-P M/NM 3H AT IP65	9W	446 Lm	50 lm/W	SO	IP65	269 x 144 x 42 mm	93529	93599
VELLA LED SC 150 M/ NM 3H AT IP65	7W	159 Lm	23 lm/W	SC	IP65	269 x 144 x 42 mm	93702	93621
VELLA LED SC 250 M/ NM 3H AT IP65	8W	287 Lm	36 lm/W	SC	IP65	269 x 144 x 42 mm	93706	93614
VELLA LED SOH 250 M/ NM 3H AT IP65	9W	346 Lm	38 lm/W	SOH	IP65	269 x 144 x 42 mm	93532	93612
VELLA LED SCH 350 M/ NM 3H AT IP65	10W	477 Lm	48 lm/W	SCH	IP65	269 x 144 x 42 mm	93718	93600
VELLA LED SCA 150 M/ NM 3H AT IP65	6W	184 Lm	31 lm/W	SCA	IP65	269 x 144 x 42 mm	93710	93619
VELLA LED SCA 250 M/ NM 3H AT IP65	8W	333 Lm	42 lm/W	SCA	IP65	269 x 144 x 42 mm	93714	93610
VELLA LED SCHA 250 M/NM 3H AT IP65	9W	336 Lm	37 lm/W	SCHA	IP65	269 x 144 x 42 mm	93722	93608



Luminaires housing elements made of high quality materials: PC/ ABS body, PC diffuser, PMMA light guide plate: colour - white or black

LiFePO4 and NiCd (only version ECO) batteries with the autonomy time 3HR

Colour temperature 5000K

All products can be used in either non-maintained or maintained mode

TEST - Autotest (AT)

DS Vella - PMMA plate	267 x 150 mm	93601
Exit left	123 x 123 mm	93334
Exit right	123 x 123 mm	93335
Arrow left / right / up / down	123 x 123 mm	93336
Arrow cross up / down	123 x 123 mm	93337
Evacuation exit	246 x 123 mm	93338
Fire hose reel	246 x 123 mm	93091
PT recessed mounting kit		94491
Suspended mounting kit	max. 2000	94490
Protective grid (silver)	340 x 200 x 62 mm	91840
Protective canopy (white)	373 x 171 x 65 mm	91844
Protective canopy (black)	373 x 171 x 65 mm	91843
0°-90° mounting support (white)	202 x 45 x 66 mm	93605
0°-90° mounting support (black)	202 x 45 x 66 mm	91992

Open spaces	SO
Corridor lens type (narrow optics)	SC
Open spaces (Power LED)	SO 350-P
High open spaces	SOH
Corridor lens type for high spaces	SCH
Asymmetric corridor lens type	SCA
Corridor lens type for high spaces, asymmetric	SCHA

Surface mounted

Recessed into the ceilings

Wall mounted