

INDIT

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	COLOUR TEMPERATURE	ORDER REFERENCE
INDIT 40	36W	3860 Lm	107 lm/W	1117 x 530 x 75 mm	3000K	INDT40
INDIT 40	36W	3940 Lm	109 lm/W	1117 x 530 x 75 mm	4000K	INDT40

*Values are given for HEX diffuser and may vary for other options

FIXINGS

	INFO	CODE
End Cap	Single/Metal*	INDI-ENDCAP
	Single/PC	INDI-ENDCAP-S
Joints	Inline	INDI-JOINT-I
	Corner 90°*	INDI-JOINT-C
	T-joint*	INDI-JOINT-T
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical*	ZLISS-SUSP

*Any RAL colour option available. Order example: **INDI-ENDCAP-GR**


MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey

DIFFUSER - PMMA

INSTALLATION

Suspended



ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Microprismatic HEX

Opal OPQ

CASING COLOUR

Grey GR

White WH

Black BL

Custom RAL

EMERGENCY MODULE

3 hr EM

Order code example: **INDT40-4K-ST-HEX-GR**