

on request

## FLYLINE

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
FLYLINE 15	13W	1400 Lm	107 lm/W	545 x 73 x 75 mm	FLYL15
FLYLINE 30	25W	2890 Lm	115 lm/W	1085 x 73 x 75 mm	FLYL30
FLYLINE 45	36W	4380 Lm	121 lm/W	1625 x 73 x 75 mm	FLYL45
FLYLINE 60	48W	5900 Lm	122 lm/W	2170 x 73 x 75 mm	FLYL60

\*Values are given for colour temperature of 4000K / HEX diffuser, and may vary for other options

### FIXINGS

	INFO	CODE
End Cap	Single*	FLYL-ENDCAP
Joints	Inline Recessed	FLYL-JOINT-I
	Corner 90°*	FLYL-JOINT-C

\*Any RAL colour option available.  
Order example: **FLYL-ENDCAP-GR**

### ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVERTYPE	
Standard	ST
Dimming - DALI	DL

DIFFUSER	
Microprismatic	HEX
Opal	OPQ
Parabolic Louvers	PAR
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL

### MATERIALS

CASING - electrostatically painted aluminium;  
standard colour - grey


DIFFUSER - PMMA

### INSTALLATION

Recessed into plaster-cardboard

### EMERGENCY MODULE

3 hr EM



Order code example: **FLYL45-4K-ST-HEX-GR-EM**