



SUPREMA LED D

PRODUCT NAME	POWER CONSUMPTION	PROTECTION LEVEL	PRODUCT SIZE	ORDER CODE FOR WHITE	ORDER CODE FOR BLACK
SUPREMA LED D-std M/NM 3H AT IP54 NT	5W	IP54	335 x 217 x 60 mm	94604	93994
SUPREMA LED D-std M/NM 3H AT IP54 PT	5W	IP54	335 x 217 x 80 mm	94654	93986
SUPREMA LED D-std M/NM 3H AT IP54 NT-S	5W	IP54	335 x 217 x 60 mm	94608	93961
SUPREMA LED D-std M/NM 3H AT IP54 PT-S	5W	IP54	335 x 217 x 80 mm	94658	93957

FIXINGS

	INFO	CODE
Flag mounting bracket, white		94494
Flag mounting bracket, black		93927
Wall mounting bracket, white		94493
Wall mounting bracket, black		93926
Suspended mounting kit		94492
Evacuation exit	300 x 150 mm	98006 / E1
Exit to the right	300 x 150 mm	98005 / E2
Exit to the left	300 x 150 mm	98004 / E3
Exit down to the left	300 x 150 mm	98003 / E4
Exit up to the left	300 x 150 mm	98002 / E5
Exit up to the right	300 x 150 mm	98001 / E6
Exit down to the right	300 x 150 mm	98000 / E7
Exit down R	300 x 150 mm	97999 / E8
Exit down L	300 x 150 mm	97998 / E9
Exit up R	300 x 150 mm	97997 / E10
Exit up L	300 x 150 mm	97996 / E11

MATERIALS

Luminaire's housing elements made of high quality materials: PC/ ABS body, PC diffuser, PMMA light guide plate: colour - white or black

LiFePO4 batteries with the autonomy time 3HR

Colour temperature 5000K

All products can be used in either non-maintained or maintained mode

TEST - Autotest (AT)

EXPLANATION

INSTALLATION TYPE

Surface mounting	NT
Recessed mounting	PT
Surface mounting with suspended light guide plate	NT-S
Recessed mounting with suspended light guide plate	PT-S

INSTALLATION

- Surface mounted
- Recessed into the ceilings
- Wall mounted
- Suspended

