



## IPSILO 1X

L90 > 100 000 h (Ts-85 °C) | CRI > 80

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
IPSILO 1X 4	80W	12715 Lm	159 lm/W	710 x 85 x 70 mm	IP1X4
IPSILO 1X 5	100W	16215 Lm	162 lm/W	890 x 85 x 70 mm	IP1X5
IPSILO 1X 6	120W	19320 Lm	161 lm/W	1060 x 85 x 70 mm	IP1X6
IPSILO 1X 7	150W	24149 Lm	161 lm/W	1230 x 85 x 70 mm	IP1X7

\*Values are given for 60° beam angle and may vary for other options

### MATERIALS

CASING - aluminum extrusion, coated.  
Mounting bracket - steel

DIFFUSER - tempered glass

### INSTALLATION

Surface mounted

Suspended (supply cable 1,00 m /  
3 pin connector)

### ORDER CODE

#### COLOUR TEMPERATURE

3000K 3K

4000K 4K

#### DRIVER TYPE

Standard ST

Dimming - DALI DL

#### BEAM ANGLE

30° 30

60° 60

90° 90

30 x 90° 30x90

#### EMERGENCY MODULE

3 hr EM

#### ADD-ONS

Motion Sensor MS



Order code example: **IP1X6-4K-DL-30-EM-MS**