



ARGO

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 83

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	DIFFUSER	PRODUCT SIZE	ORDER REFERENCE
ARGO 20	16W	1750 Lm	109 lm/W	HEX/OPQ	Ø 320 x 66 mm	ARGO20
ARGO 40	37W	3870 Lm	105 lm/W	HEX/OPQ	Ø 440 x 69 mm	ARGO40
ARGO 45	37W	4150 Lm	112 lm/W	HEX/OPQ	Ø 520 x 69 mm	ARGO45
ARGO 50	37W	4530 Lm	122 lm/W	HEX/OPQ	Ø 630 x 110 mm	ARGO50
ARGO 65	57W	6370 Lm	112 lm/W	OPQ	Ø 800 x 110 mm	ARGO65
ARGO 120	100W	12250 Lm	123 lm/W	OPQ	Ø 1065 x 110 mm	ARGO120

FIXINGS

	INFO	CODE
Suspension set	1.5m	ARGO-SP
	Ø 320	ARGO20-RM
Recessed mounting kit	Ø 440	ARGO40-RM
	Ø 520	ARGO45-RM

MATERIALS

CASING - powder painted aluminium; standard colour - grey

BASE - steel sheet


DIFFUSER - PMMA

INSTALLATION

Surface mounted

Suspended

Recessed (additional mounting bracket required)



ORDER CODE

COLOUR TEMPERATURE	
3000K	3K
4000K	4K
DRIVER TYPE	
Standard	ST
Dimming - DALI	DL
DIFFUSER	
Microprismatic	HEX
Opal	OPQ
CASING COLOUR	
Grey	GR
White	WH
Black	BL
Custom	RAL
EMERGENCY MODULE*	
3 hr	EM

*Available in ARGO40, ARGO65 and ARGO120

Order code example: **ARGO40-4K-ST-HEX-WH**