



INDI X

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	ORDER REFERENCE
INDI X 40	39W	4180 Lm	107 lm/W	1085 x 57 x 75 mm	INDX40
INDI X 60	58W	6370 Lm	109 lm/W	1625 x 57 x 75 mm	INDX60
INDI X 80	77W	8560 Lm	111 lm/W	2170 x 57 x 75 mm	INDX80

*Values are given for colour temperature of 4000K / HEX di user, and may variate for other options

MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey

DIFFUSER - PMMA

INSTALLATION

Suspended

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Microprismatic HEX

Opal OPQ

Parabolic Louvers PAR

CASING COLOUR

Grey GR


White WH

Black BL

Custom RAL

EMERGENCY MODULE

3 hr EM



Order code example: **INDX60-4K-ST-HEX-GR-EM**

End Cap	Single/Metal*	INDI-ENDCAP
	Single/PC	INDI-ENDCAP-S
Joints	Inline	INDI-JOINT-I
	Corner 90°*	INDI-JOINT-C
	T-joint*	INDI-JOINT-T
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical*	ZLISS-SUSP