



INDI C

L80 B10 > 72 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	PRODUCT SIZE	COLOUR TEMPERATURE	ORDER REFERENCE
INDI C 25	25W	2510 Lm	100 lm/W	587 x 57 x 75 mm	3000K	INDC25
INDI C 25	25W	2560 Lm	102 lm/W	587 x 57 x 75 mm	4000K	INDC25

*Values are given for HEX diffuser and may vary for other options

FIXINGS

	INFO	CODE
End Cap	Single/Metal*	INDI-ENDCAP
	Single/PC	INDI-ENDCAPS-S
Joints	Inline	INDI-JOINT-I
	Surface Mounting Bracket*	INDI-JOINT-S
	Corner 90°*	INDI-JOINT-C
	T-joint*	INDI-JOINT-T
Suspension Kit	Simple INOX	ZLISS-INOX
	Electrical*	ZLISS-SUSP

MATERIALS

CASING - electrostatically painted aluminium; standard colour - grey
DIFFUSER - PMMA

INSTALLATION

Surface mounted
Suspended

ORDER CODE

COLOUR TEMPERATURE

3000K 3K
4000K 4K

DRIVER TYPE

Standard ST
Dimming - DALI DL

DIFFUSER

Microprismatic HEX
Opal OPQ

CASING COLOUR

Grey GR
White WH
Black BL
Custom RAL



Order code example: **INDC25-4K-ST-HEX-GR**