

LIMONA

L80 B10 > 54 000h | SDCM 3 | LLMF 85% | CRI 84

PRODUCT NAME	POWER CONSUMPTION	LUMEN OUTPUT*	EFFICACY*	DIFFUSER	PRODUCT SIZE	ORDER REFERENCE
LIMONA 35	35W	3670 Lm	105 lm/W	HEX	1240 x 155 x 31 mm	LIMO35
LIMONA 35	27W	3490 Lm	129 lm/W	PAR	1240 x 155 x 31 mm	LIMO35
LIMONA 50	45W	4790 Lm	106 lm/W	HEX	1740 x 155 x 31 mm	LIMO50
LIMONA 70	51W	6970 Lm	137 lm/W	PAR	1240 x 155 x 31 mm	LIMO70

*Values are given for 4000K colour temperature and may vary for other options

MATERIALS

CASING - powder painted aluminium; standard colours - grey/black

DIFFUSER - PMMA

INSTALLATION

Suspended (suspension included)

ORDER CODE

COLOUR TEMPERATURE

3000K 3K

4000K 4K

DRIVER TYPE

Standard ST

Dimming - DALI DL

DIFFUSER

Microprismatic HEX

Parabolic Louvers PAR

CASING COLOR

Grey GR



White WH

Black BL

Custom RAL

EMERGENCY MODULE

3 hr EM



Order code example: **LIMO35-4K-ST-HEX-BL-EM**